



PRODUCT SPECIFICATIONS

UV-EXTREME

UV-EXTREME is the ultimate in exterior UV protection. Its unique polycarbonate blended urethane system offers excellent stability in exposed environments. A very flexible yet hard film stands up to the weather fluctuations without becoming brittle. Can be used over many different substrate and is available in three sheens. Dries crystal clear and remains clear over time. User friendly and easily maintainable makes this the clear choice for exterior applications.

Application: **UV-EXTREME** is designed to replace conventional solvent based finishes and as such should be sprayed or applied with a high quality nylon brush. Stir gently so as not to create air bubbles and then strain. Do not over-apply. Thin coats are better than heavy coats. Product **should not** go on looking milky. If it does you have applied too much and dry time will be lengthened substantially.

Dry Time: **UV-EXTREME** is designed to dry to sand at 75 F in less than 60 minutes. Re-coat immediately after sanding. It is safest to apply no more than 2-3 coats per day. Product must be completely dry before another coat is applied. Maximum hardness occurs after 7 days.

Note: Although rated for exterior use and much testing has been done, there are many variables which will affect the life of the product and its substrate in an exterior situation.

Clean-Up: Clean and flush all equipment with water immediately after use.

E.S.C. Coatings are designed for the professional and therefore a certain level of knowledge is assumed. When in question always do a test area. For questions please call 619-297-4421.

Warning!!! As with any product that is being sprayed into the air or applied in other manners, always use adequate ventilation and proper breathing attire.

First Aid: In case of eye contact flush with plenty of water for 15 minutes or more and seek medical attention. Wash off skin with soap and water. **DO NOT INGEST.** If this occurs seek medical attention immediately.

Gloss 90
VOC 50 g/l
Viscosity 25 Seconds #3 Zahn
Coverage 400 sq.ft. per gallon

Tack Free Time 6 minutes@ 75f
Dry to Sand 45 minutes@ 75f
Total Solids Volume 30%